

4x4

HOLDEN - GM - ISUZU












HOLD-60

















TYPE: Colorado RG  
 MODEL: RG - GM 1700,  
 MMU 142 / 143 / 145 / 147 / 148  
 YEAR: 05/2012 on  
 DETAIL: 2.8L Turbo Diesel, Single Cab / Dual Cab



This vehicle has been issued with a recall notice to change the Coil Spring Stepped Isolator. Take care when ordering Coil Springs or Shock Absorbers.

FRONT		QTY	PART NUMBER	PRICE
<b>COIL SPRING</b>				
For vehicles with the Flat Type Upper Coil Isolator				
	Linear Rate Standard Height (10mm Lift) 50-80Kg	1	<b>C59-276</b>	B
	Linear Rate Raised Height (40mm Lift)	1	<b>C59-134</b>	B
	Linear Rate Raised Height (40mm Lift) 50-100Kg	1	<b>C59-296</b>	B
Suits vehicles with the Coil Spring Stepped Isolator fitted				
	Linear Rate Standard Height (10mm Lift) 50-100Kg	1	<b>C21-382</b>	B
	Linear Rate Raised Height (40mm Lift) Up to 40Kg	1	<b>C21-384</b>	B
	Linear Rate Raised Height (40mm Lift) 50-80Kg	1	<b>C21-386</b>	B
	Linear Rate Raised Height (40mm Lift) 80-100Kg	1	<b>C21-388</b>	B
<b>SHOCK ABSORBER</b>				
	Twin Tube Gas Heavy Duty	2	<b>GS21-470</b>	
	Internal Monotube Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	<b>IMS21-50470</b>	
X - Centre of Eye to Spring Seat				
	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 190mm / 7.48"	2	<b>MR21-50470</b>	
X - Centre of Eye to Spring Seat				
<b>STRUT CAP</b>				
	Strut Top Cap	2	<b>SC59-002</b>	
Can only be used with C59-134 and C59-296				
<b>BUMP STOP</b>				
	Replacement Bump Stop Progressive Adjustable 0-20mm Extension	2	<b>BS59-560</b>	
Replaces Original Bump Stop. If Exceeding Listed Spring Seat Heights This MUST Be Used To Prevent Coil Bind.				

REAR		QTY	PART NUMBER	PRICE
<b>LEAF SPRING</b>				
	3 + 3 Leaves Medium Duty Raised Height (40mm Lift) Up to 100Kg Constant Load	2	<b>L21-140-R</b>	
	4 + 3 Leaves Heavy Duty Raised Height (40mm Lift) 250Kg Constant Load (Recommended)	2	<b>L21-141-R</b>	
	5 + 3 Leaves Super Heavy Duty Raised Height (40mm Lift) 450Kg Constant Load	2	<b>L21-142-R</b>	
	2 + 1 Leaves (Parabolic) Raised Height (50mm Lift) Up to 70Kg Constant Load Comfort Option	2	<b>L21-182-RP</b>	
<b>SHACKLE BUSH KIT</b>				
	Kit Contains: 2 x PB59-1503 4 x PB59-1530 4 x PB59-1532	1	<b>PB21-1105K</b>	
<b>U-BOLT KIT</b>				
	Suits <b>L21-140-R</b> Kit Contains: 2 x UB59-453-2	2	<b>UB59-453-2K</b>	
	Suits <b>L21-141-R</b> Kit Contains: 2 x UB59-437	2	<b>UB59-437K</b>	
	Suits <b>L21-142-R</b> Kit Contains: 2 x UB59-437	2	<b>UB59-437K</b>	
	Suits <b>L21-182-RP</b> Kit Contains: 2 x UB59-437	2	<b>UB59-437K</b>	
<b>SHOCK ABSORBER</b>				
	Twin Tube Gas Heavy Duty	2	<b>GS43-801</b>	
	Internal Monotube Heavy Duty	2	<b>IMS21-50471</b>	
	Monotube Remote Reservoir Heavy Duty	2	<b>MR43-50801</b>	
<b>SHACKLE</b>				
	Greasable: Fit in Pairs	2	<b>SK21-059</b>	
<b>PIN</b>				
	Greasable: Fit in Pairs	2	<b>SP59-060</b>	

Torsion Bars: Sold in Pairs.  
 Coil Springs: Sold in Pairs - Letter Indicates Price Code (A), (B), (C) etc.

\*Raised Height Measurements are Listed as a Guide Only. FEB20 Rev B  
 ‡All prices are in AUD and subject to change without notice.