



TYPE: X-Class
 MODEL: X 250, X 350
 YEAR: 2018 on
 DETAIL: 4x4






FRONT

QTY	PART NUMBER	PRICE
-----	-------------	-------



COIL SPRING

Due to the Restricted Suspension Geometry, a Maximum of 40mm Lift is Achievable in the Front of this Vehicle.

2.3L Turbo Diesel X 250

	Linear Rate Standard Height Heavy Duty Up to 80Kg	1	C45-254	B
	Linear Rate Raised Height (35mm Lift) Up to 50Kg	1	C45-278	B
	Linear Rate Raised Height (35mm Lift) 60-90Kg	1	C45-280	B

3.0L Turbo Diesel X 350

	Linear Rate Raised Height (30mm Lift) Up to 35Kg	1	C45-484	C
	Linear Rate Raised Height (35mm Lift) 60-90Kg	1	C45-486	C

SHOCK ABSORBER

	Internal Monotube Adjustable Spring Seat Heavy Duty Original Setting of X = 106mm / 4.17"	2	IMS45-50648	
--	---	---	--------------------	--

X - Centre of Eye to Spring Seat

	Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 106mm / 4.17"	2	MR45-50642A	
--	---	---	--------------------	--

X - Centre of Eye to Spring Seat

STRUT CAP

	Strut Top Cap	2	SC45-004	
--	---------------	---	-----------------	--

BUMP STOP

	Replacement Bump Stop Progressive Adjustable 0-35mm Extension	2	BS59-560	
--	--	---	-----------------	--







Replaces Original Bump Stop.
 If Exceeding Listed Spring Seat Heights This MUST Be Used
 To Prevent Coil Bind.

REAR




QTY	PART NUMBER	PRICE
-----	-------------	-------

COIL SPRING

Remove OE Coil Spring Insulator and Fit to Dobinsons Coil Spring

	Variable Rate Standard Height 50-150Kg Constant Load	1	C45-457V	B
	Variable Rate Standard Height Heavy Duty 150-300Kg Constant Load	1	C45-459V	B
	Variable Rate Raised Height (20mm Lift) No Load	1	C45-457V	B
	Variable Rate Raised Height (40mm Lift) Up to 80Kg Constant Load Comfort Option	1	C45-441V	B
	Variable Rate Raised Height (40mm Lift) 250-300Kg Constant Load	1	C45-443V	B
	Variable Rate Raised Height (40mm Lift) 450-550Kg Constant Load	1	C45-445V	C

SHOCK ABSORBER

	Twin Tube Gas Heavy Duty	2	GS45-646	
	Internal Monotube Heavy Duty	2	IMS45-50646	
	Monotube Remote Reservoir Heavy Duty	2	MR45-50646	

ADJUSTABLE PANHARD ROD

Adjustable Panhard Rod	1	PR45-1425	
------------------------	---	------------------	--

SWAY BAR EXTENSION & BRAKE EXTENSION BRACKET

Sway Bar Extension & Brake Extension Bracket	1	SE45-523K	
---	---	------------------	--

TRAILING ARM

Designed For More Articulation

Upper Trailing Arm

Heavy Duty Rear Upper Adjustable Control Arms (Pair) Complete With Bushes	1	WA45-541K	
---	---	------------------	--