



TYPE: Triton, L200  
 MODEL: ML, MN  
 YEAR: 05/2006 to 2015  
 DETAIL: 4x4, Warrior, 4x2 Highrider




## FRONT


QTY PART NUMBER PRICE

## COIL SPRING


Due to Vastly Different OE Ride Heights a Lift of Only 20mm May be Possible in Some Models


4x2 Highrider  
4x4 MN 2.5 T/D Single Cab Only


 Linear Rate Raised Height (40mm Lift) Up to 70Kg 1 **C43-186** B

 Linear Rate Raised Height (45mm Lift) 70-100Kg 1 **C43-192** B

4x4 ML 3.5 V6 Petrol  
4x4 MN 2.5 T/D Dual Cab GL/GLX/GLX-R


 Linear Rate Raised Height (40mm Lift) Up to 20Kg 1 **C43-192** B

 Linear Rate Raised Height (40mm Lift) 50-70Kg 1 **C43-206** B


 Linear Rate Raised Height (45mm Lift) 70-100Kg 1 **C43-188** B


## 4x4 ML 3.2 T/D

 Linear Rate Raised Height (40mm Lift) Up to 70Kg 1 **C43-188** B

 Linear Rate Raised Height (45mm Lift) 70-100Kg 1 **C43-190** B

## SHOCK ABSORBER

 Twin Tube Gas Heavy Duty 2 **GS43-800**


 Internal Monotube Adjustable Spring Seat Heavy Duty Original Setting of X = 210mm/8.26" 2 **IMS43-50800**

X - Centre of Eye to Spring Seat

 Monotube Remote Reservoir Adjustable Spring Seat Heavy Duty Original Setting of X = 210mm / 8.26" 2 **MR43-50800**

X - Centre of Eye to Spring Seat

## STRUT CAP

 Strut Top Cap 2 **SC43-005**

## TOP OUT STOP KIT

Top Out Stop Kit 1 **WA43-539K**

Recommended To Fit This Kit With All Suspension Kits To Maintain Droop Travel

## BUMP STOP

Replacement Bump Stop Progressive Adjustable 0-30mm Extension 2 **BS59-560**


Replaces Original Bump Stop.  
If Exceeding Listed Spring Seat Heights This MUST Be Used To Prevent Coil Bind.


## REAR


QTY PART NUMBER PRICE


## LEAF SPRING

After Fitting The Springs Below, We Recommend Adjusting the Brake Proportioning Valve


 3 + 2 Leaves Raised Height (40mm Lift) Comfort Spring 2 **L43-014-R**

 4 + 2 Leaves Raised Height (45mm Lift) Medium Duty 100Kg Constant Load 2 **L43-015-R**

 5 + 2 Leaves Raised Height (45mm Lift) Heavy Duty 350Kg Constant Load 2 **L43-016-R**


 6 + 2 Leaves Raised Height (45mm Lift) Extra Heavy Duty 550Kg Constant Load 2 **L43-017-R**

## SHACKLE BUSH KIT


 Kit Contains:  
2 x PB43-1508  
4 x PB43-1528  
4 x PB43-1527 1 **PB43-1085K**

## U-BOLT KIT

## 05-2006 - 04/2013


 Kit Contains:  
2 x UB43-701 2 **UB43-701K**


## 04/2013 on


 Kit Contains:  
2 x UB45-800 2 **UB45-800K**

## SHOCK ABSORBER

 Twin Tube Gas Heavy Duty 2 **GS43-801**

 Twin Tube Gas Heavy Duty, Long Travel (Big Bore) 2 **GS59-651**


 Internal Monotube Heavy Duty 2 **IMS43-50801**

 Monotube Remote Reservoir Heavy Duty 2 **MR43-50801**

## SHACKLE

 Greasable: Fit in Pairs 2 **SK43-037**

## PIN

 Greasable: Fit in Pairs 2 **SP59-060**

## TAILSHAFT SPACER

When Fitting Raised Suspension, a Tailshaft Spacer is Required to Align the Centre Bearing and Prolong Life in Models with a 2 Piece Tailshaft

Tailshaft Spacer 1 **S43-001**